

# Cisco 1600 Series Routers and WAN Interface Cards

Flexible, Secure Data Access for Small Businesses and Small Branch Offices

As companies realize the benefits of the Internet, intranets, and extranets, they require access solutions that can accommodate growth and change. The Cisco 1600 series routers deliver the flexibility, security, and functionality that small offices demand today and as networks evolve.

The Cisco 1600 series has become the proven choice for data access for small branch offices and small businesses because they offer a range of features specifically designed for such applications:

- Modular design for wide-area network (WAN) choice and flexibility
- Advanced security, including optional integrated firewall, encryption, and virtual private network (VPN) software
- End-to-end quality of service (QoS) and multimedia support
- Integrated data service unit/channel service unit (DSU/CSU) with up to T1 speed and integrated Network Termination (NT1)
- Low cost of ownership through WAN bandwidth optimization
- Ease of use, deployment, and management

The Cisco 1700 modular access router series builds upon the success of the Cisco 1600 series routers, delivering greater flexibility and investment protection. The Cisco 1700 series routers are fully modular enabling customers to tailor an access solution to serve their needs today and cost effectively add new services including voice/data integration, VPNs, and broadband connections when needed.

Cisco 1600 Series Router



Cisco 1600 Series Modular Routers  
Cisco 1600 series routers connect small offices with Ethernet LANs to WANs through Integrated Services Digital Network (ISDN), asynchronous serial, and synchronous serial connections. The five basic configurations of the Cisco 1600 product family offer the following connections:

- Cisco 1601 R—one Ethernet, one serial, one WAN interface card slot
- Cisco 1602 R—one Ethernet, one serial with integrated 56-kbps DSU/CSU, one WAN interface card slot
- Cisco 1603 R—one Ethernet, one ISDN Basic Rate Interface (BRI) (S/T interface), one WAN interface card slot

- Cisco 1604 R—one Ethernet, one ISDN BRI with integrated NT1 (U interface), one S-bus port for ISDN phones, one WAN interface card slot
- Cisco 1605 R—two Ethernet ports, one WAN interface card slot

The serial WAN port on the Cisco 1601 R router supports asynchronous serial connections of up to 115.2 kbps and synchronous serial connections—such as Frame Relay, leased lines, Switched 56, Switched Multimegabit Data Service (SMDS), and X.25—of up to 2.048 Mbps. The Cisco 1602 R router integrates a 56-kbps four-wire DSU/CSU, and it supports the same synchronous serial connections as the Cisco 1601 R router (except SMDS). The ISDN BRI port on the Cisco 1603 R router has an S/T interface, while the Cisco 1604 R includes an integrated NT1 with a U interface. The Cisco 1605 R router provides a 10BaseT and an AUI port on the first Ethernet interface and a 10BaseT port on the second Ethernet interface.

#### Modularity for Flexibility and Investment Protection

The WAN interface card slot allows customers to change or add WAN interfaces as their requirements grow or change. With this feature, the Cisco 1600 series offers more flexibility and investment protection than any other product in its class. What's more, the ability to use the same WAN interface cards in Cisco 1600, 1700, 2600, and 3600 routers reduces requirements for spare parts inventory and protects investments in existing routers.

All Cisco 1600 models support the following WAN interface cards:

- One-port serial (asynchronous and synchronous)
- One-port T1/Fractional T1 DSU/CSU
- One-port 56/64-kbps four-wire DSU/CSU

The Cisco 1601 R, Cisco 1602 R and Cisco 1605 R also accept the one-port ISDN BRI cards for dial or leased line with either S/T or U (NT1) interfaces.

#### Device Integration

Cisco 1600 routers deliver a complete solution for remote access for small businesses and small branch offices. They provide not only advanced routing capabilities but also

the option to integrate DSU/CSU and ISDN network termination 1 device (NT1), as well as firewall, encryption, and VPN functionality. This integration reduces deployment time and expense because fewer devices and cables need to be installed and configured. An integrated product also saves space and increases reliability because fewer stand alone devices are required to build the solution. The Cisco 1600 routers simplify ongoing support of small branch offices from a central site through remote configuration, monitoring, and troubleshooting of all integrated functions in the router.

#### Advanced Security

To leverage the unprecedented opportunities offered by communications and commerce over the Internet, private information must remain secure. Cisco IOS security services provide many technologies to build a custom security solution. The elements of security services include perimeter security, firewalls, encryption, and VPNs.

Perimeter Security—Perimeter security refers to the control of traffic entry and exit between network boundaries, such as between private networks, intranets, extranets, or the Internet. Cisco IOS perimeter security technologies provide a highly flexible, superior solution with features such as:

- Standard and extended access control lists (ACLs)
- Lock and Key (dynamic ACLs)
- Router/route authentication, authorization, and accounting (such as PAP/CHAP, TACACS+, and RADIUS)

Firewall—The optional Cisco IOS Firewall Feature Set, available on all Cisco 1600 models, provides formidable firewall functionality, including:

- Context-based access control (CBAC)
- Java blocking
- Attack detection and prevention
- Improved logging and alerts

CBAC provides stateful application-layer security by examining traffic sessions on a per-application basis and allowing return traffic through the firewall. When a session is initiated internally, CBAC writes a temporary, session-specific ACL entry and deletes the ACL entry upon session termination.



The Cisco 1605 R router—which supports one WAN slot, two Ethernet ports, and the Cisco IOS Firewall Feature Set—makes an ideal integrated and flexible firewall for small offices. This integrated router/firewall effectively segments an internal, secure LAN from a perimeter LAN with Web servers exposed to an untrusted network (such as the Internet), thus creating a “demilitarized zone.”

See the Cisco IOS Firewall Feature Set data sheet for further details.

**Virtual Private Networks (VPNs) and Encryption**—The Cisco 1600 series routers may be deployed as an entry-level VPN access solution, supporting DES encryption at rates of up to 128 kbps. The Cisco 1700 modular access router is recommended for VPN applications that require greater performance or 3DES or both. Cisco IOS software for the Cisco 1600 series provides a comprehensive set of VPN features, including the following key technologies:

- IPSec tunneling with data encryption standard (DES)
- Layer 2 Forwarding (L2F) and Layer 2 Tunneling Protocol (L2TP)
- VPN management tools such as support for VPN policy configuration in Cisco ConfigMaker

**Cisco IOS Software Features for Small Office Internet/Intranet Access**

Cisco 1600 series routers offer small businesses and small branch offices a complete set of internetworking software features. In addition to the features mentioned earlier, Cisco IOS software differentiates the Cisco 1600 series from the competition with:

- Multiprotocol routing (IP, IPX, AppleTalk), IBM/SNA, and transparent bridging over ISDN, asynchronous serial, and synchronous serial such as leased lines, Frame Relay, SMDS, Switched 56, X.25, and X.25 over D
- Network Address Translation (NAT), which eliminates the need to re-address all hosts with existing private network addresses and hides internal addresses from public view.
- Easy IP—a combination of NAT, Point-to-Point Protocol/Internet Control Protocol (PPP/ICP) and Dynamic Host Configuration Protocol (DHCP) server—which enables the router to dynamically negotiate its own IP address and dynamically allocate local IP addresses to the remote LAN hosts, simplifies deployment, and minimizes Internet access costs

- End-to-end QoS features that include Resource Reservation Protocol (RSVP), IP Multicast, WFQ, and AppleTalk Simple Multicast Routing Protocol (SMRP), which support multimedia applications such as desktop videoconferencing, distance learning, and voice/data integration
- WAN optimization features such as dial-on-demand routing (DDR), bandwidth-on-demand (BOD), and Open Shortest Path First (OSPF)-on-demand circuit, Snapshot routing, compression, filtering, and spoofing to reduce WAN costs

**Ease of Use and Deployment**

The Cisco 1600 series includes a variety of easy, user-friendly installation and configuration features such as color coded ports, removable Flash memory PC cards for easy software deployment, the Cisco ConfigMaker configuration tool and the Cisco Fast Step™ software tool. These features combine to give the lowest total cost of ownership of any small office router.

Each Cisco 1600 series router includes the Cisco Fast Step easy-to-use Windows 95, 98, and NT 4.0-based software tool that simplifies the setup, monitoring, and troubleshooting of Cisco routers. The Cisco Fast Step setup application leads users through simple, step-by-step, wizards-based procedures to configure Cisco routers connected to an Internet service provider and remote corporate network. Cisco Fast Step software includes the Cisco Fast Step monitor application, which provides users with router LAN and WAN performance statistics, fault alarms, and troubleshooting assistance.

The Cisco ConfigMaker application is appropriate for advanced configuration of the Cisco 1600 series routers. A Windows 95, 98, 2000, and NT 4.0-based software tool, Cisco ConfigMaker is designed to configure a small network of Cisco routers, switches, hubs, and other network devices from a single PC. Cisco ConfigMaker is designed for resellers and network administrators of small and medium-sized businesses who are proficient in LAN and WAN fundamentals and basic network design. Cisco ConfigMaker includes support for the Cisco IOS Firewall Feature Set (which provides integrated enhanced security capabilities), Network Address Translation (NAT), and Cisco Easy IP software.

In addition to easy-to-use software, the hardware for the Cisco 1600 routers is designed to be “plug-and-play” in four notable areas. First, each of the ports on the Cisco 1600 routers and WAN interface cards is color coded, and optional color-coded cables can be purchased from Cisco. Second, preconfigured software may be loaded into a Flash memory PC card at a central site, and then a user at remote site may deploy the router by simply inserting the Flash card, plugging in cables, and turning on the power. Third, once the router is running, software upgrades and configuration modifications can be downloaded over the WAN from a central site. And finally, the Cisco 1600 series allows for centralized administration and management via Simple Network Management Protocol (SNMP) or Telnet or through the console port.

Part of the Cisco Networked Office  
 The Cisco 1600 series is part of the Cisco Networked Office (CNO) stack, a suite of flexible and integrated products designed to provide complete networking solutions for small businesses and small branch offices. Other compatible products in the CNO stack include the Cisco 1720 router, Cisco 1528 Micro Hub 10/100, Cisco 1538 Micro Hub 10/100, Cisco 1548 Micro Switch 10/100, Cisco IOS Firewall, and Cisco ConfigMaker software.

## Technical Specifications

### Cisco 1600 Product Family

	Cisco 1601 R Models	Cisco 1602 R Models	Cisco 1603 R Models	Cisco 1604 R Models	Cisco 1605 R Models
<b>First Fixed Interface (LAN)</b>	Ethernet: 10Base-T (RJ-45) and AUI (DB-15)				
<b>Second Built-In Interface (WAN or LAN)</b>	Serial Sync/ Async: DB-60	56K 4-wire DSU/ CSU: RJ-48S	ISDN BRI S/T: RJ-45	ISDN BRI U with NT1: RJ-45	Ethernet: 10Base-T (RJ-45) Only
<b>WAN Interface Card Slot</b>	All Models				
<b>Optional WAN Interface Cards</b>					
Serial Sync/Async	Yes	Yes	Yes	Yes	Yes
T1/FT1 DSU/CSU	Yes	Yes	Yes	Yes	Yes
56/64K DSU/CSU	Yes	Yes	Yes	Yes	Yes
ISDN BRI S/T	Yes	Yes	—	—	Yes
ISDN BRI U	Yes	Yes	—	—	Yes
ISDN BRI Leased Line S/T	—	—	Yes	Yes	—
<b>Processor</b>	Motorola 68360 at 33 MHz				
<b>Memory Architecture</b>	Run-from-RAM				
<b>DRAM: Default</b>	8 MB				
<b>DRAM: Maximum</b>	24 MB				
<b>Flash Memory: Default</b>	4 MB				
<b>Flash Memory: Maximum</b>	16 MB				
<b>Console Port</b>	RJ-45				



WAN Interface Cards

Product Number	Interfaces	Supported Cisco 1600 Models
WIC-1T	one-port, serial, async, and sync (T1/E1)	All
WIC-1DSU-T1	one-port, T1/fractional T1 DSU/CSU	All
WIC-1DSU-56K4	one-port, 56/64-kbps 4-wire DSU/CSU	All
WIC-1B-S/T	one-port, ISDN BRI S/T (dial and leased line)	Cisco 1601 R, Cisco 1602 R, and Cisco 1605 R
WIC-1B-U	one-port, ISDN BRI U with NT-1 (dial and leased line)	Cisco 1601 R, Cisco 1602 R, and Cisco 1605 R
WIC-1B-S/T-LL	one-port, ISDN BRI S/T (leased line only)	Cisco 1603 R and Cisco 1604 R

The ISDN BRI leased line S/T card (WIC-1B-S/T-LL) is designed specifically for the Cisco 1603 R and 1604 R routers. It is intended for users who require a dialup ISDN BRI line (from the Cisco 1603 R or 1604 R router fixed-WAN port) and an ISDN leased line (from the ISDN BRI leased line card inserted into the Cisco 1603 R or 1604 R router). This card is automatically configured only in ISDN leased line mode. ISDN leased line is also known as ISDN Digital Subscriber Loop (IDSL).

Serial Interfaces Supported by the Cisco 1601 R and 1602 R Routers and Serial WAN Interface Cards

	Cisco 1601 R Onboard WAN	Cisco 1602 R Onboard WAN (four-wire)	WIC-1T Card	WIC-1DSU-56 K4 Card (four-wire)	WIC-IDSU-T1 Card
Asynchronous Serial Connection over Basic Analog Telephone	Up to 115.2 kbps	Not supported	Up to 115.2 kbps	Not supported	Not supported
<b>Synchronous Serial Connections</b>					
Leased Line / Digital Data Service (DDS)	Up to 2.0 Mbps with external DSU/CSU	56 kbps	Up to 2.0 Mbps with external DSU/CSU	56 or 64 kbps	NX56 or NX64 (N=1 to 24)
Switched 56	56 kbps with external DSU/CSU	56 kbps	56 kbps with external DSU/CSU	56 kbps	Not applicable

- Asynchronous serial protocols: Point-to-Point Protocol (PPP), Serial Line Internet Protocol (SLIP)
- Asynchronous interface: EIA/TIA-232
- Synchronous serial WAN services: Frame Relay, X.25, SMDS
- Synchronous serial protocols: PPP, HDLC, LAPB, IBM/SNA
- Synchronous serial interfaces supported on Cisco 1601 R and WIC-1T card: EIA/TIA-232, V.35, X.21, EIA/TIA-449, EIA-530

Feature	Cisco 1603 R/ 1604 R Onboard WAN	WIC-1B-S/T Card	WIC-1B-U Card	WIC-1B-S/T-LL Card
ISDN Dialup	Yes	Yes	Yes	Not supported
ISDN Leased Line 64 kbps (IDSL)	Yes	Yes	Yes	Yes*
ISDN Leased Line 128 kbps (IDSL)	Rel 11.3(1)T	Rel 11.3(1)T	Rel 11.3(1)T	Rel 11.3(3)T*
Frame Relay Encapsulation over ISDN Leased Line (IDSL)	Yes	Yes	Yes	Yes
PPP Encapsulation over ISDN Leased Line (IDSL)	Yes	Yes	Yes	Yes
PPP Compression (up to 4:1)	Yes	Yes	Yes	Yes

\* 64-kbps ISDN leased-line support on the WIC-1B-S/T-LL card is available on B1 channel only. 128-kbps ISDN leased line support on the WIC-1B-S/T-LL leased line card in Cisco IOS Release 11.3(3)T.

### Memory and Software

The Cisco IOS software image is stored in Flash memory (in compressed form), but is loaded into RAM before being executed by the router.

The 1600 series Run-from-RAM models offer the following benefits:

- **Greater Performance:** The Cisco 1600 R models deliver greater performance for memory-intensive applications such as encryption and compression.
- **Easier Upgradability:** The Cisco 1600 R routers permit software upgrades over any interface while the router is running.
- **Lower Cost:** Because the Cisco 1600 R models store the software in compressed form in flash memory, less flash memory is required to run advanced feature sets (such as Cisco 1600 series IOS IP Plus).

The available software feature sets for the Cisco 1600 R models are listed below:

Minimum Memory Requirements and Software Feature Sets for Cisco IOS Release 12.0 and 12.0T

Cisco 1601 R - 1605 R		
	Flash	DRAM
IP	4 MB	8 MB
IP/IPX	4 MB	8 MB
IP Plus	4 MB	10 MB
IP Plus 40	4 MB	10 MB
IP Plus 56	4 MB	10 MB
IP Plus IPSec 56	4 MB	12 MB
IP/IPX/AppleTalk/IBM	4 MB	12 MB
IP/IPX/AppleTalk/IBM Plus	6 MB	16 MB
IP Firewall	4 MB	8 MB
IP/IPX Firewall Plus	4 MB	10 MB
IP Firewall Plus IPSec	4 MB	12 MB
IP/IPX/AppleTalk/IBM/Firewall Plus IPSec 56	6 MB	16 MB



Starting with Cisco IOS software Release 12.0, the base feature sets include some features formerly in Plus: Network Address Translation (NAT), Open Shortest Path First (OSPF), Remote Access Dial-In User Service (RADIUS), and Next Hop Resolution Protocol (NHRP). Plus feature sets contain all the features in their corresponding base feature sets as well as an additional value-added features such as Layer 2 Tunneling Protocol (L2TP), Layer 2 Forwarding (L2F), Border Gateway Protocol (BGP), IP Multicast, Frame Relay switched virtual circuit (SVC), Resource Reservation Protocol (RSVP), NetWare Link Services Protocol (NLSP), AppleTalk Simple Multicast Routing Protocol (SMRP), and Network Timing Protocol (NTP).

Software Feature Sets Part Numbers, Cisco IOS Release 12.0

Feature Set	Cisco 1601 R–1605 R	CDs for All Models
IP	S16RC-12.0.X	CD16-C-12.0=
IP/IPX	S16RB-12.0.X	CD16-B-12.0=
IP Plus	S16RCP-12.0.X	CD16-CP-12.0=
IP Plus 40	S16RCW-12.0.X	CD16-CW-12.0=
IP Plus 56	S16RCY-12.0.X	CD16-CY-12.0=
IP Plus IPSec 56	S16RCL-12.0.X	CD16-CL-12.0=
IP/IPX/AppleTalk/IBM	S16RQ-12.0.X	CD16-Q-12.0=
IP/IPX/AppleTalk/IBM Plus	S16RQP-12.0.X	CD16-QP-12.0=
IP Firewall	S16RCH-12.0.X	CD16-CH-12.0=
IP/IPX Firewall Plus	S16RBHP-12.0.X	CD16-BHP-12.0=
IP Firewall Plus IPSec	S16RCHL-12.0.X	CD16-CHL-12.0=
IP/IPX/AppleTalk/IBM/Firewall Plus IPSec 56	S16RQHL-12.0.X	CD16-QHL-12.0=

#### Dimensions and Weight Specifications

	Cisco 1600 Series	WAN Interface Cards
Width	11.15 in. (28.32cm)	3.1 in. (7.9 cm)
Height	2.19 in. (5.56 cm)	0.8 in. (2.1 cm)
Depth	8.67 in. (22.02 cm)	4.8 in. (12.2 cm)
Weight (minimum)	1.65 lb. (0.75 kg)	0.13 lb (57 g)
Weight (maximum)	1.80 lb. (0.82 kg)	0.19 lbs (85 g)

Power Requirements for Cisco 1600 Series

Output, Watts	27 W maximum
AC Input Voltage	100 to 240 VAC
Frequency	50 to 60 Hz
AC Input Current	0.2 to 0.4 Amps

Environmental Specifications for Cisco 1600 Series and WAN Interface Cards

Operating Temperature	32 to 104 F (0 to 40 C)
Nonoperating Temperature	- 4 to 149 F (-20 to 65 C)
Relative Humidity	10% to 85% noncondensing operating; 5% to 95% noncondensing non-operating

Regulatory Compliance for Cisco 1600 Series and WAN Interface Cards

Safety

- UL 1950
- CSA 22.2 No 950
- EN60950
- EN41003
- AUSTEL TS001
- AS/NZS 3260
- ETSI 300-047
- BS 6301 (power supply)

EMI

- AS/NRZ 3548 Class A
- Class B

- FCC Part 15 Class B
- EN60555-2 Class B
- EN55022 Class B
- VCCI Class II
- CISPR-22 Class B

Immunity

- 55082-1 Generic Immunity Specification Part 1: Residential and Light Industry
- IEC 1000-4-2 (EN61000-4-2)
- IEC 1000-4-3 (ENV50140)
- IEC 1000-4-4 (EN61000-4-4)
- IEC 1000-4-5 (EN61000-4-5)
- IEC 1000-4-6 (ENV50141)
- IEC 1000-4-11
- IEC 1000-3-2

Network Homologation

Europe	CTR2,CTR3
Canada	CS-03
United States	FCC Part 68
Japan	Jate NTT
Australia/New Zealand	TS-013
Hong Kong	CR22

Bellcore Compliance

The Cisco 1604 R router is certified under Bellcore Easy ISDN codes (formerly known as ISDN Ordering Codes or IOCs).



Corporate Headquarters  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

European Headquarters  
Cisco Systems Europe  
11, Rue Camille Desmoulins  
92782 Issy-les-Moulineaux  
Cedex 9  
France  
www-europe.cisco.com  
Tel: 33 1 58 04 60 00  
Fax: 33 1 58 04 61 00

Americas Headquarters  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-7660  
Fax: 408 527-0883

Asia Pacific Headquarters  
Cisco Systems Australia, Pty., Ltd  
Level 17, 99 Walker Street  
North Sydney  
NSW 2059 Australia  
www.cisco.com  
Tel: +61 2 8448 7100  
Fax: +61 2 9957 4350

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the Cisco Web site at [www.cisco.com/go/offices](http://www.cisco.com/go/offices)

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Czech Republic • Denmark • Dubai, UAE Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam •

All contents are Copyright © 1992-2001 Cisco Systems, Inc. All rights reserved. Important Notices and Privacy Statement. Printed in the USA. Fast Step is a trademark; and Cisco, Cisco IOS, Cisco Systems, and Cisco Systems logo are registered trademarks of Cisco Systems, Inc. or its affiliates in the U.S. and certain other countries. All other brands, names, or trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0102R)